

A

01/05/98
09003003, 010598

Form No. 20350
WNSSEND and TOWNSEND and CREW LLP
Embarcadero Center, 8th Floor
San Francisco, CA 94111-3834

ASSISTANT COMMISSIONER FOR PATENTS
BOX PATENT APPLICATION
Washington, D. C. 20231

Atty. Docket No. 017096-000210
"Express Mail" Label No. EM575720852US
Date of Deposit January 5, 1998

I hereby certify that this is being deposited with the
United States Postal Service "Express Mail Post Office
to Addressee" service under 37 CFR 1.10 on the date indicated above
and is addressed to:

Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

By 

Sir:
Transmitted herewith for filing under 37 CFR §1.53(b) is the
[] patent application, [X] continuation patent application,
[] divisional patent application of

Inventor(s)/Applicant Identifier: Michael J. Dietz, II

For: ELECTRONIC SECOND SPIN SLOT MACHINE

- [X] This application claims priority from each of the following Application Nos./filing dates:
08/571,743 / December 13, 1995; _____ / _____; _____ / _____, the
disclosure(s) of which is (are) incorporated by reference.
- [] Please amend this application by adding the following before the first sentence: --This application is a [] continuation [] continuation-in-part
of and claims the benefit of U.S. Provisional Application No. 60/_____, filed _____, the disclosure of which is incorporated by
reference.--


Enclosed are:

- [x] 5 sheet(s) of [x] formal [] informal drawing(s).
[] An assignment of the invention to INFINITY GROUP, INC. .
[x] A [] signed [x] unsigned Declaration & Power of Attorney.
[] A [] signed [] unsigned Declaration.
[] A Power of Attorney by Assignee with Certificate Under 37 C.F.R. Section 3.73(b).
[X] A verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27 [] is enclosed [X] was filed in the prior application
and small entity status is still proper and desired.
[] A certified copy of a _____ application.
[x] Information Disclosure Statement under 37 CFR 1.97.
[] Enclosed is a petition to extend time to respond in the parent application.
[] Notification of change of [] power of attorney [] correspondence address filed in prior application.

In view of the Unsigned Declaration as filed with this application and pursuant to 37 CFR §1.53(d), Applicant requests
deferral of the filing fee until submission of the Missing Parts of Application.

DO NOT CHARGE THE FILING FEE AT THIS TIME.

Telephone: (415) 576-0200
Facsimile: (415) 576-0300
H:\DOCS\GWC\17096\210\NOFEE.TRN


Gay W. Chambers
Reg. No.: 30,617
Attorneys for Applicant

PATENT APPLICATION

ELECTRONIC SECOND SPIN SLOT MACHINE

Inventors:

Michael J. Dietz II, a citizen
of the United States, residing at
7 Tildios, Peralta, New Mexico 87042

Entity: Small

Guy W. Chambers, Esq.
TOWNSEND and TOWNSEND and CREW
Two Embarcadero Center, 8th Floor
San Francisco, California 94111
Telephone: (415) 576-0200

5

ELECTRONIC SECOND SPIN SLOT MACHINE

10 This is a continuation-in-part of U.S. Patent
Application Serial No. 08/571,743, filed December 13, 1995,
which is now U.S. Patent No. 5,704,835.

TECHNICAL FIELD OF THE INVENTION

15 The present invention relates to a type of gaming
machine which is commonly referred to as a slot machine. More
particularly, the present invention relates to an electronic
slot machine which allows players to select for respin one or
more of the symbols displayed after the machine's first spin.
20 This feature allows the player to get a second chance at
creating, improving or even losing a winning combination.

BACKGROUND OF THE INVENTION

25 Over the years, many games of chance have been
devised to allow players to wager a sum of money and have the
opportunity to win greater sums of money. Such games include
lotteries, bingo, keno, blackjack, poker, roulette, craps and
slot machines.

30 Of these games, many people find slot machines to be
the most entertaining. In a basic mechanical slot machine,
the player inserts a bill or coin and pulls down on the slot
machine handle to initiate the game. Three parallel,
rotatable reels with an assortment of fruit, number and/or bar
symbols are then caused to spin until each reel reaches a
35 resting position. The success or failure of the game is then
determined by comparing the combination of reel symbols across
a horizontal row with a table of winning combinations posted
on the slot machine. To add interest to the game, the basic
mechanical slot machine windows are frequently made large
40 enough to show three adjacent symbols on each reel and thereby
allow betting involving multiple rows. This betting can take

the form, for example, of betting on the combinations formed across the upper horizontal row, middle horizontal row and lower horizontal row. Betting along diagonal lines intersecting these rows is also made possible. Because the combination of symbols on each reel of a basic mechanical slot machine is fixed, there is typically no betting on vertical column combinations in the basic mechanical slot machine.

With the advent of electronic technology, there have been many improvements to the basic slot machine. Among these improvements are the use of video monitors to display an imitation of three parallel, rotatable reels, rather than having three actual reels themselves. In operation, these electronic slot machines simulate the rotation of a physical reel, but typically select the final symbols through use of random numbers generated by a microprocessor rather than any physical rotation of a reel. In other words, the final symbols for each simulated reel in the electronic slot machine are randomly selected by the microprocessor and then displayed on the video monitor at the appropriate time and position.

The use of electronic technology for slot machines has allowed additional improvements to slot machine play. For example, the number of combinations that can be displayed on a video monitor is no longer limited by the number of symbols that can be fit onto three physical reels. This opportunity for greater numbers of displayed combinations has led the way to greater jackpots and progressive slot machines. Also, with electronic technology, the three symbols shown in each column no longer need to correspond to three adjacent symbols on a physical reel. Through generation of different random numbers, each symbol displayed in a video monitor column can be independently generated. By independently generating each of the symbols shown on the video monitor, betting along vertical columns as well as horizontal rows and diagonal lines has now become feasible.

One frequent frustration that players have with slot machines, even the new electronic slot machines, is that the combination which is finally displayed along their betting line may fall just short of a winning combination and the

player has no opportunity for adjusting the displayed combination, short of completely starting a new game. To address this frustration, some mechanical slot machines allow a player to "nudge" one of the reels so that the displayed symbol is moved one notch and replaced by an adjacent symbol on the reel which is visible to the player. The success or failure of the game is then redetermined based upon the combination appearing after one of the reels has been "nudged."

While the "nudging" feature does help overcome some of the frustration of being one symbol short of a winning combination, it provides only limited relief. For example, if the next symbol on the particular reel will not create a winning combination, then there is no reason to "nudge" and have that next symbol included in the displayed combination. Also, to the extent the symbol to be nudged into place is visible, it is fairly obvious to the player whether or not to nudge. For this reason, use of a "nudging" feature adds very little additional interest to the game and, moreover, is unlikely to allow such slot machines to be reclassified from a game of "chance" to a game of "skill" in those jurisdictions which prohibit games of "chance."

SUMMARY OF THE INVENTION

The present invention provides an electronic slot machine which allows a player to completely respin one or more of the symbols displayed after the first spin in order to create, improve or even lose a winning combination. In its preferred form, the electronic slot machine of the present invention features a video monitor with a plurality of symbol display boxes arrayed in rows and columns. When the machine is activated through, for example, insertion of a valid coin and pressing of the "spin" button, one or more random numbers are generated in the slot machine's microprocessor and compared to one or more reel strips encoded in computer memory to determine which symbols are to be displayed in each of the symbol display boxes. If a desirable winning combination is not formed after this first spin, the player is given an

opportunity to select one or more of the symbol display boxes, rows of symbol display boxes or columns of symbol display boxes for respin. Where a touchscreen is used in conjunction with the video monitor, the player can make this selection simply by touching the boxes, rows of boxes or columns of boxes to be respun. After an appropriate number of boxes are chosen for respin, one or more additional random numbers are generated and compared with reel strips encoded in the computer memory to determine which new symbols are to be displayed in each of the selected boxes. After the new symbols are displayed in the selected boxes, the microprocessor compares the displayed symbols with a memorized list of winning combinations to determine if the game is a winner. If a winning combination is formed, the microprocessor determines the appropriate payout for the winning combination and provides the player with that payout.

There are, of course, numerous respin options that are enabled by the apparatus of the present invention. For example, if a symbol after the first repin turns out to be the same as the original symbol, that symbol can be respun again, either automatically or at the player's option, in order to try to obtain a different symbol. Alternatively, having the same symbol appear again after a respin could be used as an opportunity for allowing the player to have a second chance to respin any of the other symbols. As a second alternative, color backgrounds could be added to each of the symbol boxes and serve as an additional criteria for respinning to achieve winning combinations.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a front view of a preferred form of electronic second spin slot machine of the present invention.

FIG. 2 shows a typical video screen display for the electronic second spin slot machine of FIG. 1.

FIG. 3 is a block diagram which schematically shows the control system for the electronic second spin slot machine of FIG. 1.

FIG. 4 illustrates a typical reel strip which can be encoded into the slot machine's computer memory.

FIG. 5 is a flow chart for the sequence of play in the preferred form of electronic slot machine.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

Referring now to FIG. 1, a preferred form of electronic second spin slot machine 10 of the present invention is shown. Like slot machines generally, this preferred form of second spin slot machine collects money, initiates game play, illustrates game play and provides a payout for successful game play. For this particular slot machine, a bill validator 12 is provided to accept money in slot 14 in the form of bills of various denominations. A suitable bill validator for the second spin slot machine 10 of the present invention is the DBV145 bill validator manufactured by JCM of Kanagawa and Osaka, Japan. The bill validator 12 pulls in the bills, determines the denomination of the bills and determines whether the bills are valid. If a bill is invalid, it will be returned to the player back through slot 14. To the extent valid bills are inserted into the bill validator 12, bill validator 12 will retain them and communicate their presence to the slot machine's microprocessor 15 (FIG. 3), which is located on computer motherboard 16. Alternatively, a coin acceptor 17 and hopper 18 (FIG. 3) could be used to collect coins, count them, validate them and store them. Again, the information about the amount and validity of coins ascertained by the coin acceptor 17 is communicated to the slot machine's microprocessor 15. As a second alternative, the bill validator 12 can be configured to accept credit cards issued by the casino, such as a SMARTCARD™, or by multinational corporations, such as VISA™ or AMERICAN EXPRESS™ cards.

If sufficient bills, coins or credits have been inserted into the slot machine 10, the slot machine's microprocessor 15 (FIG. 3) will allow game play to be initiated. In the preferred embodiment, a "spin" button 22 located on the slot machine's button panel 20 will be lit and

enabled by the microprocessor 15. This "spin" button 22 serves as a switch to allow the player to initiate game play simply by pressing it. Additional buttons 24, 26, 28 are also located on the button panel 20 of the slot machine 10 to allow the player to call the attendant 24, cash out any accumulated winnings 26 or make multiple bets before initiating game play 28. These additional buttons 24, 26, 28 are also lit during game play, particularly when their functions are available for activation by the player.

Turning to FIG. 2, a close up of the video monitor 30 which illustrates game play is shown. In the preferred embodiment, nine symbol display boxes 32 are shown on the video monitor 30 arrayed in three rows and three columns. Each symbol display box 32 preferably shows a full symbol 34 in the center of the display box 32 and partial symbols 36, 38 in the upper and lower peripheries of the display box 32. This combination of full 34 and partial symbols 36, 38 in each display box 32 gives the appearance that each display box is showing a section of an imaginary mechanical reel. In popular slot machine use, these symbols typically take the form of fruit symbols, such as cherries, plums and oranges, as well as non-fruit symbols, such as bars, bells and sevens.

As one alternative embodiment, the partial symbols can be omitted altogether, with only the full symbols 34 being shown. This alternative embodiment would give the appearance that each column of three display boxes shows a section of an imaginary mechanical reel. This would be especially true where the horizontal lines between the symbols in each column, as shown in FIG. 2, are removed so that each column appears to be a continuous mechanical reel. Also, when the symbols in this alternative embodiment are spun, the symbols which are higher in each column should appear to move downward as they would when a mechanical reel is spun. As a second alternative embodiment, the display boxes 32 could be arrayed in different configurations of rows and columns, such as two rows and five columns. As a third alternative, background colors (not shown) could be added to each of the display boxes 32. These

background colors could serve as an additional, and possibly independent, basis for creating winning combinations.

Various straight lines 40, 42 and 44 criss-cross the display boxes 32 in horizontal 40, diagonal 42 and vertical 44 directions to illustrate to the player the various combinations of symbols that can be bet. In the preferred embodiment, a betting box 48 is provided at one end of each line where the player can signify which lines are to be bet. In alternative embodiments, the player can not only bet across lines 40, 42 and 44, but can also bet on combinations of all the displayed symbols (e.g., 8 or 9 of a kind) or various other non-linear combinations of symbols (e.g., four corners or criss-crossing symbols).

If a touch screen 50 is used in conjunction with the video monitor 30, these betting boxes 48 can appear to the player to be placed on the video monitor 30 itself. Suitable touch screens 50 for use with the present invention include the TRUEPOINT capacitive sensing screen produced by MicroTouch Systems, Inc. of Methuen, Massachusetts and the INTELLITOUCH acoustic wave sensing screen produced by ELO TouchSystems of Oak Ridge, Tennessee. In the Microtouch touch screen 50, voltage is applied to all four corners of the screen. When the player's finger touches a point on the screen, the player's finger draws current from each side of the screen in proportion to the distance from the edge of the screen. A touch screen controller can then calculate the position of the finger from the current flows. Using such a touch screen 50, the player can simply touch the betting boxes corresponding to the lines he wants to bet before pressing the "spin" button 22 on the button panel 20. Alternatively, if a touch screen 50 is not used, additional buttons can be placed on the button panel 20 and electrically connected to the microprocessor 15 to act as switches which allow the player to signify which lines he wants to bet.

FIG. 3 is a block diagram which schematically shows the control system for the electronic second spin slot machine 10 of the present invention. At the heart of this control system is the microprocessor 15. Suitable microprocessors

include the Z80 microprocessor manufactured by Zilog, Inc. of Campbell, California and the PENTIUM microprocessor manufactured by Intel Corporation of Santa Clara, California. The microprocessor 15 relies upon programming instructions stored in code read-only memory (ROM) 55 to execute the game play sequence and appropriate video displays. The code ROM 55 might suitably be a WSIPSD512 chip produced by WaferScale Integration, Inc. of Fremont, California.

When game play is initiated by pressing the spin button 22, the microprocessor 15 uses information stored in the video card 54 to simulate a symbol spinning motion in all the display boxes 32. In the preferred embodiment, the video card 54 contains a symbol graphic erasable, programmable read-only memory (EPROM), a static graphics EPROM and a random access memory (RAM). At the same time, the microprocessor 15, in conjunction with a separate RAM 56, generates one or more random numbers which will be used to designate the symbols to be displayed after the first spin. This RAM 56 may suitably take the form of a non-volatile 384K RAM chip. A real time clock 57 may advantageously be used to help the microprocessor 15 generate random numbers by tying the random number generation algorithm to the time of day. This real time clock 57 can also be helpful in generating game histories for storage in RAM 56 or transmission through network communications 59. A suitable real time clock 57 for the present electronic second spin slot machine would be a 2K non-volatile "Dallas Timekeeper" RAM produced by Dallas Semiconductor of Dallas, Texas.

To select the displayed symbols, the microprocessor 15 compares the random numbers generated with a corresponding list of symbols stored in the imaginary reel read-only memory (ROM) 58. The imaginary reel ROM 58 might suitably be a 256K EPROM.

FIG. 4 illustrates how random numbers 1 through 50 might correspond to a group of symbols including sevens, bars, oranges, plums, cherries and bells. For example, if the random number generated by the microprocessor is 24, the corresponding symbol selected from the imaginary reel strip

shown in FIG. 4 would be a "plum." To add interest to the game, the imaginary reel strips are typically much longer than 50 numbers and may advantageously have 256 numbers for use with a 256K EPROM.

If background colors are used in the display boxes 32, random numbers could be generated for these colors and compared to reel strips incorporating color designations. The randomly selected colors could then be superimposed behind the symbols in the applicable display box 32. Such randomly generated background colors could be used to create winning combinations either independently or in conjunction with the symbols contained in the display boxes 32.

The number of random numbers and imaginary reel strips which must be used to select a sufficient number of symbols and/or background colors to fill the nine display box arrangement shown in FIG. 2 varies depending upon how the random numbers and reel strips are used. In one preferred embodiment, twelve random numbers and four reel strips are used to determine the combination of symbols displayed in the nine display boxes 32 after the first spin. In this embodiment, one random number and one reel strip are used to determine the full symbols displayed in each column. The reel strip symbol corresponding to the particular random number chosen is displayed as a full symbol in the top box of the column, the next symbol down on the imaginary reel strip is displayed as the full symbol in the middle box and the symbol which is two down is displayed as the full symbol in the lower box. Referring again to the reel strip shown in FIG. 4, if the random number chosen by microprocessor 15 for the left column were an 8, the full symbol in the upper box would be a "bell", the full symbol in the middle box would be a "bar" (9) and the full symbol in the lower box would be a "cherry" (10).

After full symbols are chosen for each of the display boxes 32 in this manner, nine additional random numbers can be generated and compared to a fourth imaginary reel strip to select the partial symbols displayed in each of the nine boxes. For each of the nine random numbers, the reel strip symbol corresponding to the particular random number

5

10

15

20

25

30

35

5
10
15

20
25
30
35

respin, the player might simply touch the selected display box 32, row of display boxes 32 or column of display boxes 32 and automatically begin the respin process, without the need to touch an additional "respin" box 62.

Where background colors are used in the display boxes 32, the player might be given the option of respinning symbols in the display box, respinning background colors in the display box or both. A switch could be provided either on the touchscreen 50 or console (not shown) to allow the player to designate whether he is choosing symbols, background colors or both for respin. When this switch is used, the illumination of either the symbols or the background colors in the display boxes could increase in order to confirm to the player whether he is designating symbols or colors for respin.

When the respin box 62 is pressed by the player after an appropriate designation of display boxes 32 to be respun, the microprocessor 15 and video card 54 will again simulate spinning symbols in those boxes and only those boxes. By contrast, the non-designated boxes will continue to display their first spin results in stationary form. While spinning is being simulated in the boxes selected for respin, the microprocessor 15 will again be producing random numbers and using those random numbers to select new symbols to be displayed from the imaginary reel ROM 58. In the preferred embodiment, a single imaginary reel strip is dedicated to the selection of respun symbols. The imaginary reel strip symbol corresponding to the selected random number is displayed as the full symbol in the respin display box 32, with the imaginary reel strip symbols above and below the selected full symbol on the imaginary reel strip being shown as partial symbols in that display box 32. Of course, the same sort of alternatives for selecting the displayed symbols for the first spin can also be used in selecting displayed symbols for respin. Since a full imaginary reel strip is used in this embodiment to select replacement symbols, it is possible, unlike video poker, to randomly select replacement symbols which are the same as the initially displayed symbols that the player wants to replace.

After the respin full and partial symbols are selected by the microprocessor 15, the microprocessor instructs the video card 54 to stop the spinning symbol simulation and display the selected symbols in the appropriate respin boxes. At this point, the microprocessor can determine whether the game is a winner or loser by comparing the combination of full symbols displayed on the video screen with the betting lines 40, 42, 44 the player has selected and the combination of winning symbols stored in a read-only memory, such as the code ROM 55. If the microprocessor 15 determines that there is a winning combination on one or more of the lines 40, 42, 44 that the player has bet, the microprocessor 15 then refers to a payout table stored in an appropriate read-only memory, such as the code ROM 55, to determine the amount the player has won. The combination of winning symbols and their respective payouts should also be displayed in written form 60 on the face of the slot machine 10 to allow the player to confirm the determinations made by the microprocessor 15.

If the game is a winning game, the amount of the player's winnings will be noted as a credit 63 on the video monitor 30. If the player desires, he can press the cash out 26 button on the button panel 20 to redeem this credit. In the preferred embodiment, the redemption takes the form of a printed sheet issued by printer 64 (FIGS. 1 and 3) and provided to the player through payout tray 66. Where the second spin slot machine uses coins, the microprocessor 15 can activate coin hopper 18 to count out an appropriate number of coins and return them to the player through payout tray 66. To add excitement and interest to the game, the microprocessor 15 can activate lights 68 and a sound generator (FIGS. 1 and 3) to announce that the player has won the game.

After the game has been completed, the microprocessor 15 stores the results of the game in RAM 56 for later analysis and resets for initiation of a new game. The applicable sequence of play is summed up in flow chart form in FIG. 5.

To allow predictability of payout for the slot machine owner, the number of display boxes that can be respun each game is preferably limited to one. This limiting of respin boxes also can increase the amount of skill that must be applied by the player to select the best box for respin. Unlike games such as video poker, the electronic second spin slot machine of the present invention adds additional challenges to the player using multiple betting lines 40, 42, 44 by requiring that player to think in multiple dimensions. For example, choosing a respin of the center display box 32 can simultaneously affect combinations along two diagonal lines, one horizontal line and one vertical line. Similarly, choosing a respin of a corner display box 32 can simultaneously affect combinations along a diagonal, a horizontal and a vertical line. Additional complication and skill can be added to the slot machine game of the present invention by allowing players to bet additional lines after the first spin has taken place but before boxes are designated for respin.

While limiting the respin to one box is the preferred embodiment, there are many respin variations which would nonetheless be within the scope of the present invention. For example, the preferred embodiment described thus far allows only one round of respinning symbols. If desired, multiple rounds of choosing symbols for respin could also be allowed. With such multiple rounds, the player could view the results of the first respin round and choose additional display boxes to be respun in a second round. Further interest could be added to this multiple round respin by requiring the player to fund and redesignate betting lines 40, 42, 44 before each respin round. With multiple respin rounds and renewed betting before each respin round, a game could conceivably be continued indefinitely.

A more limited form of multiple round respin could occur only if the respun symbol turns out to be the same as the original symbol that the player was trying to replace. This frustrating scenario could be turned to the player's advantage in any number of ways. For example, the respun

symbol could be automatically, or at the player's option, respun one more time or continually respun until a different symbol appears. Alternatively, if confronted with the same symbol reappearing, the player could be given the option of respinning the symbols in different boxes or be given the option of respinning all of the symbols which are identical to the continually reappearing symbol.

Additionally, the electronic second spin slot machine apparatus of the present invention could be used for games which do not require a second spin. For example, in the touch screen embodiment of the present invention, the player could be given the opportunity to touch two different symbols from the first spin display and switch their position. Alternatively, a tenth randomly generated symbol could be added to the display shown in FIG. 2 and the player given the opportunity to substitute this tenth symbol for one of the other nine symbols.

In the foregoing specification, the invention has been described with reference to specific preferred embodiments and methods. It will, however, be evident to those of skill in the art that various modifications and changes may be made without departing from the broader spirit and scope of the invention as set forth in the appended claims. Further examples of such modifications include allowing the player to designate which symbols to keep rather than designate which symbols to respin. In this embodiment, all the symbols which are not chosen will be respun. As an additional modification, the originally displayed symbols could be preselected, as in a pull-tab game, rather than being the result of a random number generator. In a further modification of the embodiment where the player can choose only one box for respin, the apparatus of the present invention could also respin all other boxes which have the same full symbol as the one box chosen for respin. In this embodiment, for example, if the player chooses a box for respin with a plum symbol, all other boxes with a plum symbol would simultaneously be respun. The specification and drawings are, accordingly, to be regarded in an illustrative,

WHAT IS CLAIMED IS:

1. A method of operating an electronic gaming apparatus having a plurality of symbols arrayed in multiple symbol columns and rows on its monitor comprising the steps of:

selecting initial symbols to be arrayed in said multiple symbol columns and rows;

displaying the initial symbols selected in an array of multiple symbol columns and rows on said monitor;

designating a chosen number of said initial displayed symbols for replacement;

selecting said chosen number of replacement symbols;

replacing said chosen number of initial symbols on said monitor with replacement symbols;

determining whether said replacement symbols and remaining initial symbols constitute a winning combination; and,

rewarding a winning combination.

2. The method of claim 1 wherein game play can only be commenced if it is determined that an appropriate amount of money has been inserted into the gaming apparatus.

3. The method of claim 1 wherein said symbols are randomly selected by a microprocessor.

4. The method of claim 1 wherein symbols can be designated for replacement and be replaced on multiple occasions before it is determined whether a winning combination exists.

5. The method of claim 1 wherein the option is provided of designating no symbols for replacement.

6. The method of claim 1 wherein only one symbol can be designated for replacement.

7. The method of claim 1 wherein multiple symbols can be designated for replacement.

8. The method of claim 1 wherein a list of winning combinations is stored in a memory and compared to the combination displayed on said monitor to determine if there is a winning combination.

9. The method of claim 8 wherein winning combinations are determined by evaluating the symbols displayed across one or more rows.

10. The method of claim 8 wherein winning combinations are determined by evaluating the symbols displayed across one or more columns.

11. The method of claim 8 wherein said initial and replacement symbols are selected by generating random numbers and comparing those random numbers to numbered positions on a list of symbols.

12. The method of claim 1 wherein said initial and replacement symbols are selected by choosing symbols from a fixed position on a periodically shuffled list of symbols.

13. The method of claim 1 wherein each said replacement symbol may be the same as the initial symbol it replaces.

14. The method of claim 13 wherein said replacement symbol may be itself replaced if it is the same as the initial symbol it replaces.

15. The method of claim 14 wherein said replacement symbol may be itself replaced at the player's option if it is the same as the initial symbol it replaces.

5 16. The method of claim 14 wherein said replacement symbol will be automatically replaced if it is the same as the initial symbol it replaces.

10 17. The method of claim 6 wherein all symbols which are the same as the one symbol designated for replacement are also replaced.

15 18. A method of operating an electronic gaming apparatus having a plurality of symbols and background colors arrayed in columns and rows on its monitor comprising the steps of:

 selecting initial symbols and initial background colors for said symbols to be so arrayed in said multiple symbol columns and rows;

20 designating a chosen number of said initial symbols and initial background colors for replacement;

 selecting said chosen number of replacement symbols and background colors;

25 replacing said chosen number of initial symbols and initial background colors on said monitor with replacement symbols and replacement background colors; and,

30 determining whether said replacement symbols and replacement background colors together with the remaining initial symbols and initial background colors constitute a winning combination; and,

 rewarding a winning combination.

35 19. The method of claim 18 wherein said replacement background colors are chosen independently of said replacement symbols.

365970" E00E0050

20. An electronic gaming apparatus comprising:
a monitor for displaying a plurality of symbols
arrayed in multiple symbol columns and rows;

a memory which stores a list of possible
symbols to be displayed on said monitor;

a microprocessor to select symbols from said
memory for display on said monitor and to determine
whether a final group of displayed symbols creates a
winning or losing game;

a first switch to initiate game play by causing
the microprocessor to select an initial set of symbols
and display those initial symbols arrayed in multiple
symbol columns and rows on said monitor; and,

a second switch to complete game play by always
allowing the player to choose for replacement at least
one, but not all, of said initial symbols and have said
microprocessor randomly select said replacement symbols
from a full list of possible symbols in said memory and
then display on said monitor said replacement symbols
together with the remaining initial symbols to create
said final group of displayed symbols arrayed in multiple
symbol columns and rows.

21. The electronic gaming apparatus of claim 20
wherein said player chooses initial symbols for replacement by
simply designating which initial symbols to replace.

22. The electronic gaming apparatus of claim 20
wherein said player chooses initial symbols for replacement by
designating which initial symbols should be kept and then
allowing said electronic gaming apparatus to replace all non-
designated symbols.

23. The electronic gaming apparatus of claim 20
wherein said player can designate one or more columns of
initial symbols for replacement.

5 25. The electronic gaming apparatus of claim 20
wherein said player can designate one or more rows of initial
symbols for replacement.

27. The electronic gaming apparatus of claim 20
further including a touch screen which is electronically
connected to said microprocessor.

29. The electronic gaming apparatus of claim 20 wherein only one symbol is chosen for replacement.


25 30. The electronic gaming apparatus of claim 20
wherein multiple symbols are chosen for replacement.

ELECTRONIC SECOND SPIN SLOT MACHINEABSTRACT OF THE DISCLOSURE

5 An electronic slot machine (10) and method of use
which allows a player to completely respin one or more of the
symbols displayed after the first spin in order to create,
improve or even lose a winning combination. In its preferred
form, the electronic slot machine of the present invention
10 features a video monitor (30) with a plurality of symbol
display boxes (32) arrayed in rows and columns. When the
machine is activated through, for example, insertion of a
valid coin and pressing of the "spin" button (22), one or more
random numbers are generated in the slot machine's
15 microprocessor (15) and compared to one or more reel strips
encoded in computer memory (58) to determine which symbols are
to be displayed in each of the symbol display boxes. If a
suitable winning combination is not formed after this first
spin, the player is given an opportunity to select one or more
20 of the symbol display boxes for respin. After the new symbols
are selected by the microprocessor and displayed in the respun
boxes, the microprocessor compares the displayed symbols with
a memorized list of winning combinations to determine if the
game is a winner.

25

865070-6005060






FIG. 2.




FIG. 3.

	4/5		
seven	:1	bell	:41
seven	:2	seven	:42
seven	:3	plum	:43
bar	:4	orange	:44
orange	:5	bar	:45
plum	:6	plum	:46
cherry	:7	bell	:47
bell	:8	plum	:48
bar	:9	plum	:49
cherry	:10	bar	:50
orange	:11		
orange	:12		
bell	:13		
plum	:14		
orange	:15		
bell	:16		
seven	:17		
bell	:18		
plum	:19		
bell	:20		
orange	:21		
plum	:22		
bar	:23		
plum	:24		
seven	:25		
bell	:26		
plum	:27		
orange	:28		
bar	:29		
bell	:30		
cherry	:31		
plum	:32		
bar	:33		
bell	:34		
orange	:35		
orange	:36		
plum	:37		
plum	:38		
orange	:39		
bar	:40		

FIG. 4.




FIG. 5.

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **ELECTRONIC SECOND SPIN SLOT MACHINE** the specification of which ___ is attached hereto or X was filed on January 5, 1998 as Application No. ___ and was amended on ___ (if applicable).

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56. I claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign applications(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Country	Application No.	Date of Filing	Priority Claimed Under 35 USC 119
			Yes _ No _
			Yes _ No _

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below:

Application No.	Filing Date

I claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application No.	Date of Filing	Status
08/571,743	12/13/95	<u>x</u> Patented _ Pending _ Abandoned
		_ Patented _ Pending _ Abandoned

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Guy W. Chambers, Reg. No. 30,617
James F. Hann, Reg. No. 29,719
Philip A. Albert, Reg. No. 35,819

Send Correspondence to: Guy W. Chambers TOWNSEND and TOWNSEND and CREW LLP Two Embarcadero Center, 8th Floor San Francisco, CA 94111-3834	Direct Telephone Calls to: (Name, Reg. No., Telephone No.) Name: Guy W. Chambers Reg. No.: 30,617 Telephone: (415) 576-0200
---	--

Full Name of Inventor 1	Last Name DIETZ	First Name MICHAEL	Middle Name or Initial J., II	
Residence & Citizenship	City Peralta	State/Foreign Country New Mexico	Country of Citizenship USA	
Post Office Address	Post Office Address 7 Tildos	City Peralta	State/Country New Mexico	Zip Code 87042
Full Name of Inventor 2	Last Name	First Name	Middle Name or Initial	
Residence & Citizenship	City	State/Foreign Country	Country of Citizenship	
Post Office Address	Post Office Address	City	State/Country	Zip Code
Full Name of Inventor 3	Last Name	First Name	Middle Name or Initial	
Residence & Citizenship	City	State/Foreign Country	Country of Citizenship	
Post Office Address	Post Office Address	City	State/Country	Zip Code

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Signature of Inventor 1 Michael J. Dietz, II	Signature of Inventor 2	Signature of Inventor 3
Date	Date	Date